

<b>MATERIAL SAFETY Data Sheet</b>	EMERGENCY PHONE NUMBER	HAZARD RATING 4=EXTREME 3=HIGH 2=MODERATE 1=SLIGHT 0=INSIGNIFICANT **SEE SECTION V	
	800.346.9090		

### I. General Information

Manufacturer <b>ULTRASEAL INTERNATIONAL, INC. 1100 N. WILCOX AVENUE LOS ANGELES, CA 90038</b>	TRADE NAMES & SYNONYMS <b>ULTRASEAL TIRE SEALANT – P/N's 5511/5150/5110 and 5110T</b>		
DOT Hazard classification	<b>NOT HAZARDOUS</b>	Chemical family	<b>MIXTURE</b>
Proper DOT Shipping Name <b>COMPOUND, FLUID, NOIBN</b>			
Prepared By: <b>D.C. ATKINS &amp; SON, INC.</b> Date: <b>January 1, 2012</b>		<b>LEGEND:</b> N/E = Not Established N/A = Not Applicable	

### II. Ingredients

Hazardous Compounds	CAS Number	Percent	ACGTH TLV
<b>ETHYLENE GLYCOL</b>	<b>107-21-1</b>	<b>&lt;30</b>	<b>50 ppm</b>

### III. Physical Data

Boiling Point (def. F): <b>121-127°C, (250-260°F)</b>	Specific Gravity (H2O=1): <b>1.08</b>
Vapor Pressure ( mm Hg @ 20°C (68°F): <b>&lt;20 mm HG</b>	Percent Volatile: <b>92</b>
Vapor Density (Air=1): <b>1.3</b>	Evaporation Rate (water+1): <b>Approximately 1.0</b>
Solubility in Water: <b>Approximately 90% soluble</b>	Reactivity in Water: <b>NONE</b>
Appearance & Odor: <b>VISCOUS FIBER SUSPENSION, MILD ODOR</b>	pH: <b>8.5-9.0</b>

### IV. Fire & Explosion Hazard Data

Flash Point (Test Method) SetaFlash Closed Tester <b>NONE</b>	Flammable Limits UEL <b>NE</b> LEL <b>NE</b>
	Auto Ignition Temperature <b>NE</b>
Extinguishing Media <input checked="" type="checkbox"/> Foam <input type="checkbox"/> Alcohol Foam <input checked="" type="checkbox"/> CO2 <input type="checkbox"/> Dry Chemical <input checked="" type="checkbox"/> Water Spray <input checked="" type="checkbox"/> Water <input type="checkbox"/> Not Applicable <input type="checkbox"/> Other	
Special Fire Fighting Procedures: <b>NONE</b>	
Unusual Fire & Explosion Hazards <b>NONE</b>	

### V. Health Hazard Data

Threshold Limit Value of Product

**OSHA TEV**

**ACGTH TLV**  
See section II

Carcinogen  
**NONE KNOWN**

#### SYMPTOMS OF EXPOSURE AND ROUTES OF

EYES: IRRITATION  
SKIN: POSSIBLE IRRITATION ON PROLONGED CONTACT  
INHALATION: IRRITATION TO RESPIRATORY TRACT  
INGESTION: IRRITATION TO THE GASTROINTESTINAL TRACT

#### FIRST-AID MEASURES

EYES: FLUSH WITH WATER FOR 15 MINUETS. CONSULT A PHYSICIAN IF IRRITATION PERSISTS  
SKIN: WASH WITH SOAP AND WATER. REMOVE CONTAMINATED CLOTHING AND FOOTWEAR  
INHALATION: REMOVE TO FRESH AIR  
INGESTION: GIVE TWO GLASSES OF WATER. INDUCE VOMITING, CALL A PHYSICIAN IMMEDIATLEY

### VII. Reactivity Data

Stability	<input type="checkbox"/> Unstable <input checked="" type="checkbox"/> Stable	Conditions to Avoid
Incompatibility		Materials to Avoid NONE
Hazardous Polymerization	<input type="checkbox"/> May Occur <input checked="" type="checkbox"/> Will Not Occur	Conditions to Avoid N/A

Hazardous Decomposition Products

#### OXIDES OF CARBON ON INCINERATION

### VII. Environmental Protection Procedures

Spill Response

**SMALL SPILL:** WIPE UP  
**LARGE SPILL:** DIKE AREA. PUMP INTO TANK FOR RECOVERY OR DISPOSAL

Waste Disposal Method

INCINIRATE IN ACCORDANCE WITH APPLICABLE LOCAL, STATE AND FEDERAL REGULATIONS

### VIII. Special Protection Information

Eye Protection <b>NOT NORMALLY NEEDED</b>	Skin Protection <b>NOT NORMALLY NEEDED</b>
Respiratory Protection (specific type) <b>NOT NORMALLY NEEDED</b>	Ventilation Recommended <b>GENERAL</b>
Other Protection <b>MATERIAL IS SLIPPERY</b>	

### IX. Special Precautions

Hygienic Practices in Handling & Storage

**STORE IN DOORS**

OTHER PRECAUTIONS **KEEP CLOSURES ON CONTAINERS WHEN NOT IN USE**

DISPOSAL OF EMPTY CONTAINERS

**FLUSH WITH WATER BEFORE DISPERSING.**

**SHELF LIFE IS 5 YEARS**